



VNS-10WR2

10.1" ultra slim Panel PC

- > RockChip RK3568 Cortex-A55, Quad Core up to 2.0GHz
- > 2GB / 4GB RAM
- > 32GB eMMC
- > PCAP Touch
- > 10/100/1000 Ethernet
- > Touch button (Power/ Brightness/ Volume/ LED)
- > RS232, RS422 or RS485
- > DC 12~24V Input or Powered LAN 802.3at
- > NFC Reader
- > D-MC
- > 2.0MP Camera
- > Speak 4Ω 2.0W
- > LED Indicating Light Bar
- > 75 x 75mm VESA Mount
- > Plastic has Antibacterial

+ Spec

-System Information-	
Processor	RockChip RK3568 Cortex-A55, Quad Core up to 2.0GHz
System Memory	2GB / 4GB DDR4 RAM
Storage	
Storage	32GB eMMC
Panel	
LCD Size	10.1"
Resolution	1280x800
Luminance	350
Viewing angle	170° (H/V)
Touch Type	PCAP
I/O	
USB Port	2 x USB 2.0
External I/O Connector	1 x RJ45 for RS232, RS422 or RS485 2 x USB 2.0 Type A 1 x 10/100/1000 Ethernet 1 x 4-Pin 3.5mm Audio Jack
Camera	2.0MP Camera
System Control	
LED Indicator	Light color: 24-bit / true color Illuminating area: 70*8mm(front),70*5mm(side)
Data Collection	
Camera	2M pixel
NFC	NFC Reader
Wireless Communication	
WLAN	802.11 b/g/n
Display	
Spec. & Resolution	LVDS: Max. resolution 1280x800 @ 60Hz
Audio	
Speaker Output	4Ω 2.0W/2.2W(MAX)
Certifications	
Certification Information	CE, FCC Class B
Ethernet	
LAN Chipset	Realtek RTL8211F-CG
LAN Port	1 x RJ45
Power Requirement	
Adapter	Input: 100~240 Vac/50~60 Hz Output: 60W Adapter (12V @ 5A Adapter)
Mechanical & Environmental	
Operating Temperature	0°C ~ 40°C
Storage Temperature	-10°C ~ 60°C
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	1.1 kg
VESA	75 x 75
Power Requirement	DC Input, 12~24V
Power Mode	DC jack or Powered LAN 802.3at
Dimension (L x W)	270 x 193 x 28 mm
Software Support	
OS Information	Android 11, Debain 11