



LPC-1209

12.1" Intel® Atom™ SoC Processor E3845 Fanless Rugged Touch Panel PC

- > Intel® Atom™ E3845 1.91GHz CPU
- > One 204-pin DDR3L SODIMM Socket Supports Up to 8GB DDR3L 1333 SDRAM
- > 1 CF, 2 USB, 1 COM
- > Dual Intel I210IT Gigabit LAN
- > Wide Voltage +12V ~ +26V Input, ErP Power
- > Backlight Controlled by PWM
- > IP65 Compliant Front Panel
- > Timer-Power-On

+ Spec

System	
Processor	Intel® Atom™ E3845 4-Core 1.91GHz processor
System Memory	1 x 204-Pin DDR3L 1333MHz SO-DIMM up to 8 GB
I/O Chip	EC ITE IT8528E
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec./1sec.step
H/W Status Monitor	Monitoring SYSTEM Temperature and Voltage with Auto Throttling Control
SBC	EBM-BYT
Expansion	
Expansion	1 x Mini PCIe Support mSATA 1 x Mini PCIe Supports SIM Card
Storage	
Storage	1 x CompactFlash Type VII Socket 1 x 2.5" Drive Bay
I/O	
USB	1 x USB 3.0 1 x USB 2.0
SATA	1 x SATA II
COM Port	1 x RS-232/422/485 (BIOS)
Other	1 x HDMI 1 x Knockouts for Antenna Mounting
Display	
Chipset	Intel® Valleyview SoC integrated Graphics Supports dual display
Resolution	HDMI:Max. resolution 1920x1200@ 60Hz
Audio	
Chipset	Realtek ALC892
Audio Interface	Line-Out
Ethernet	
Chipset	2 x Intel® I210IT
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45
Mechanical & Environmental	
Operating Temp	-20°C ~ 60°C (-4°F ~ 140°F)
Storage Temp	-30°C ~ 70°C (-22°F ~ 158°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Weight	2.84Kgs
Dimension (L x W x H)	283 x 222 x 45 mm
Vibration Test	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
System Fan	Fanless
Construction - Front	Silver Aluminum
Construction - Rear	Black
Certifications	
Certification Information	CE / FCC Class B
Software Support	
OS Information	Win 7 Win 8 Linux
Power Requirement	
Power Connector	Lockable DC Jack



Power Requirement	+12V ~ +26V
Power Mode	AT/ATX (ATX is default setting)
Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter)
Panel	
LCD Size	12.1", 4:3
Display Type	XGA
Resolution	1024 x 768
Pixel pitch	0.240mm(H) x 0.240mm(V)
Luminance	600 cd/m2
Contrast ratio	700
Viewing angle	70 (U), 70 (D), 80 (L), 80 (R)
Response time	16 ms
Backlight	LED
Touch Type	5 Wires resistive
Touch Light Transmission	80%
Touch Controller	Onboard USB touch (EETI)

+ Ordering

LPC-1209-384-B1R
Intel Atom E3845 1.91GHz CPU/4G DDR3L/2GLAN/COM/12~26V input/12V Adaptor

ACC-LPC-WIFIUSB-3R
USB WiFi 802.11 b/g/n Module w/ Antenna, Cable

ACC-ARM-D22R
VESA STAND, 75x75 & 100x100 mm

ACC-ARM-D29R
ARM A800B VESA standard 75*75 & 100*100mm

ACC-LPC-12-PMT-02R
Back Panel Mount Kit for LPC-12 Series, w/IP-65